

LONG LASTING SPRAY PAINT

TECHNICAL DATA SHEET
Version 5.0 – Revised 2025

Product Description

Long lasting spray paint for coating interior/exterior surfaces providing excellent coverage. Used on construction materials, decorative elements & for advertisement purposes. Available in a wide color variety.

Approvals



Features

- Quick to dry
- Easy to apply
- Weather resistant
- High coverage
- Interior/Exterior application
- CFC free
- Superior adhesion



**WEATHER
RESISTANT**



**QUICK
TO DRY**



**HIGH
COVERAGE**




**SUPERIOR
ADHESION**




LONG LASTING
SPRAY PAINT

TECHNICAL DATA SHEET
Version 5.0 – Revised 2025

Packaging



Shelf Life



Standard Colors



Technical Data

Property	Unit	Value
Resin Type		Acrylic
Base		Solvent Based
Touch to Dry	Mins	5
Inner Pressure	MPa	0.42 ± 0.10
Spray Rate	%	≥ 97
Leak Test		Negative
Application Temperature	°C	10 – 35
Temperature Resistance	°C	80

Instructions

Shake can vigorously for at least one minute after rattling of mixing ball is heard. While in use, shake intermittently to ensure color uniformity and to prevent clogging.

Hold the can approximately 30 cm from the object to be sprayed. Press spray button firmly while moving can back and forth. Finger must not protrude over front edge of spray button at any time.

Keep can in level line with surface and do not apply continuous spray. For best results, apply 2 to 3 thin coats with intermittence of 10 minutes. Once applied, if product were to bubble, foam or run then you are too close to the surface or coat is too heavy.

After use, clear out the paint can’s nozzle. To do so, hold the can upside down, depress the nozzle and keep spraying until only gas emerges.

Safety Precautions

Keep upright and away from children

Can contents under pressure. Do not puncture or burn. Shelter from direct sunlight. Do not store at temperatures exceeding 50°C.

The information in this document is based on Saber Industrial’s technical and practical experience. It is provided for reference only and may not include all relevant details. Users must test product suitability for their intended application, surface, and conditions. Saber Industrial accepts no liability for misuse, improper application, storage, or transport. We reserve the right to change formulations without notice. Warranty is limited to conformance with current sales specifications. Liability is restricted to refund or replacement of non-conforming product.

