

DRY WALL JOINT COMPOUND

- ◆ UP TO 5 MM
- ◆ HIGH ADHESIVE THICKNESS STRENGTH
- ◆ HIGH FILLING POWER
- ◆ EASY SANDING
- ◆ WHITE AND FINE



PURPOSE

Ready to use dry wall joint compound to be used in association with a joint tape, interior use, manual application. Can also be used as finish surface filler.

SUBSTRATES

J-MIX can be applied on any type of plasterboards with thin edges with or without insulating parts and plaster carton boards.

OVERCOATING

J-MIX can be coated with a primer or a surface filler.

PHYSICAL AND TECHNICAL FEATURES

J-MIX: filler in paste form for interior use, made of mineral components and synthetic resin.

- Characterization (NFT 36-005): Family III - Class 2.
- Codification (EN 16566): $G_3S_1V_0W_0A_0C_0R_0$
- Application thickness: up to 5 mm.
- Consumption: approx. 300 gr/m².
- Overcoat: when fully dry (depends on the thickness which has been applied).
- Colour: white.
- Adhesion filler/substrate (EN 16566): > 0.5 Mpa.

USE AND STORAGE CONDITIONS

- Application tools: with smoothing or surfacing blade.
- Tools cleaning: with water.
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from frost and sun.

RECOMMENDATIONS AND CARE FOR USE

- Do not apply under a temperature below 8°C and above 35°C nor under a hygrometry rate over 70%.
- Do not apply on overheated surfaces.
- Do not apply on polystyrene, on damp substrates nor on wall paper, nor on exterior substrates.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS TO BE REFERRED TO

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).
- NF Environment – Paint fillers (NF446).
- NFT 36-005: Characterization of paint products.

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Interior Filler.

Always wear a dust mask when sanding.

Dispose of unused product and packaging responsibly at your local waste collection centre.

- No danger tag.
- Very low VOC emissions : < 0,02 %.

Safety data sheet available at www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).

Official distributor :

ATLANTIS BUILDING MATERIALS TRADING (LLC)
PO BOX 214873 DUBAI UNITED ARAB EMIRATES
Tel : +97143405648 / +971558938809 Fax: +97143405649
E-mail: info@atlantis4arch.ae

KASSA'A PAINTS GROUP
COLOURTEK Bldg
PO BOX 14-5592 MSAYTBEH STREET – BEIRUT – LEBANON
Tel : +961 1 305649 -306966- 303414 E-mail : toupretme@toupret.com

